

	ASM #	Half Shaft Splines	Outer CV Splines	Inner CV Splines	Plunge/Angle Diagram																																																												
<b>Outlaw</b>	1521150	<table border="1"> <tr><td colspan="2">HARDENED SPLINE INTERFACE (TYP.)</td></tr> <tr><td colspan="2">ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT</td></tr> <tr><td>NO. OF TEETH</td><td>20</td></tr> <tr><td>PITCH</td><td>24/48</td></tr> <tr><td>PRESSURE ANGLE</td><td>45°</td></tr> </table>	HARDENED SPLINE INTERFACE (TYP.)		ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT		NO. OF TEETH	20	PITCH	24/48	PRESSURE ANGLE	45°	<table border="1"> <tr><td colspan="2">EXTERNAL INVOLUTE SPLINE (ANSI-B92.1) FILLET ROOT SIDE FIT CLASS 7</td></tr> <tr><td>NO. OF TEETH</td><td>23</td></tr> <tr><td>PITCH</td><td>24/48</td></tr> <tr><td>PRESSURE ANGLE</td><td>45°</td></tr> <tr><td>PITCH DIAMETER</td><td>.9583 REF.</td></tr> <tr><td>BASE DIAMETER</td><td>.6776 REF.</td></tr> <tr><td>FORM DIAMETER</td><td>.929</td></tr> <tr><td>MAJOR DIAMETER</td><td>1.000/0.990</td></tr> <tr><td>MINOR DIAMETER</td><td>.902 MIN.</td></tr> <tr><td colspan="2">CIRC. TOOTH THICKNESS</td></tr> <tr><td>MAX. EFFECTIVE</td><td>.0738</td></tr> <tr><td>MIN. ACTUAL</td><td>.0685</td></tr> <tr><td>MIN. MEASUREMENT OVER PINS</td><td>1.0855</td></tr> <tr><td>PIN DIA.</td><td>.080</td></tr> </table>	EXTERNAL INVOLUTE SPLINE (ANSI-B92.1) FILLET ROOT SIDE FIT CLASS 7		NO. OF TEETH	23	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	.9583 REF.	BASE DIAMETER	.6776 REF.	FORM DIAMETER	.929	MAJOR DIAMETER	1.000/0.990	MINOR DIAMETER	.902 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0685	MIN. MEASUREMENT OVER PINS	1.0855	PIN DIA.	.080	N/A																							
HARDENED SPLINE INTERFACE (TYP.)																																																																	
ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT																																																																	
NO. OF TEETH	20																																																																
PITCH	24/48																																																																
PRESSURE ANGLE	45°																																																																
EXTERNAL INVOLUTE SPLINE (ANSI-B92.1) FILLET ROOT SIDE FIT CLASS 7																																																																	
NO. OF TEETH	23																																																																
PITCH	24/48																																																																
PRESSURE ANGLE	45°																																																																
PITCH DIAMETER	.9583 REF.																																																																
BASE DIAMETER	.6776 REF.																																																																
FORM DIAMETER	.929																																																																
MAJOR DIAMETER	1.000/0.990																																																																
MINOR DIAMETER	.902 MIN.																																																																
CIRC. TOOTH THICKNESS																																																																	
MAX. EFFECTIVE	.0738																																																																
MIN. ACTUAL	.0685																																																																
MIN. MEASUREMENT OVER PINS	1.0855																																																																
PIN DIA.	.080																																																																
<b>RZR S Rear</b>	1332883		<table border="1"> <tr><td colspan="2">WHEEL HUB INTERFACE</td></tr> <tr><td colspan="2">EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT</td></tr> <tr><td>NO. OF TEETH</td><td>26</td></tr> <tr><td>PITCH</td><td>24/48</td></tr> <tr><td>PRESSURE ANGLE</td><td>45°</td></tr> <tr><td>PITCH DIAMETER</td><td>1.0833 REF.</td></tr> <tr><td>BASE DIAMETER</td><td>.766 REF.</td></tr> <tr><td>FORM DIAMETER</td><td>1.0560</td></tr> <tr><td>MAJOR DIAMETER</td><td>1.1250/1.1150</td></tr> <tr><td>MINOR DIAMETER</td><td>1.0320 MIN.</td></tr> <tr><td colspan="2">CIRC. TOOTH THICKNESS</td></tr> <tr><td>MAX. EFFECTIVE</td><td>.0738</td></tr> <tr><td>MIN. ACTUAL</td><td>.0702</td></tr> <tr><td>MIN. MEAS. OVER PINS</td><td>1.2135 REF.</td></tr> <tr><td>PIN DIAMETER</td><td>.080</td></tr> </table>	WHEEL HUB INTERFACE		EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT		NO. OF TEETH	26	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	1.0833 REF.	BASE DIAMETER	.766 REF.	FORM DIAMETER	1.0560	MAJOR DIAMETER	1.1250/1.1150	MINOR DIAMETER	1.0320 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0702	MIN. MEAS. OVER PINS	1.2135 REF.	PIN DIAMETER	.080	<table border="1"> <tr><td colspan="2">DIFFERENTIAL INTERFACE</td></tr> <tr><td colspan="2">ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)</td></tr> <tr><td>NO. OF TEETH</td><td>27</td></tr> <tr><td>PITCH</td><td>24/48</td></tr> <tr><td>PRESSURE ANGLE</td><td>45°</td></tr> <tr><td>PITCH DIAMETER</td><td>1.1250 REF.</td></tr> <tr><td>BASE DIAMETER</td><td>.7955 REF.</td></tr> <tr><td>FORM DIAMETER</td><td>1.0960</td></tr> <tr><td>MAJOR DIAMETER</td><td>1.1670/1.1570</td></tr> <tr><td>MINOR DIAMETER</td><td>1.0740 MIN.</td></tr> <tr><td colspan="2">CIRC. TOOTH THICKNESS</td></tr> <tr><td>MAX. EFFECTIVE</td><td>.0738</td></tr> <tr><td>MIN. ACTUAL</td><td>.0700</td></tr> <tr><td>MIN. MEAS. OVER PINS</td><td>1.2542 REF.</td></tr> <tr><td>PIN DIAMETER</td><td>.080</td></tr> </table>	DIFFERENTIAL INTERFACE		ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)		NO. OF TEETH	27	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	1.1250 REF.	BASE DIAMETER	.7955 REF.	FORM DIAMETER	1.0960	MAJOR DIAMETER	1.1670/1.1570	MINOR DIAMETER	1.0740 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0700	MIN. MEAS. OVER PINS	1.2542 REF.	PIN DIAMETER	.080	
WHEEL HUB INTERFACE																																																																	
EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT																																																																	
NO. OF TEETH	26																																																																
PITCH	24/48																																																																
PRESSURE ANGLE	45°																																																																
PITCH DIAMETER	1.0833 REF.																																																																
BASE DIAMETER	.766 REF.																																																																
FORM DIAMETER	1.0560																																																																
MAJOR DIAMETER	1.1250/1.1150																																																																
MINOR DIAMETER	1.0320 MIN.																																																																
CIRC. TOOTH THICKNESS																																																																	
MAX. EFFECTIVE	.0738																																																																
MIN. ACTUAL	.0702																																																																
MIN. MEAS. OVER PINS	1.2135 REF.																																																																
PIN DIAMETER	.080																																																																
DIFFERENTIAL INTERFACE																																																																	
ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)																																																																	
NO. OF TEETH	27																																																																
PITCH	24/48																																																																
PRESSURE ANGLE	45°																																																																
PITCH DIAMETER	1.1250 REF.																																																																
BASE DIAMETER	.7955 REF.																																																																
FORM DIAMETER	1.0960																																																																
MAJOR DIAMETER	1.1670/1.1570																																																																
MINOR DIAMETER	1.0740 MIN.																																																																
CIRC. TOOTH THICKNESS																																																																	
MAX. EFFECTIVE	.0738																																																																
MIN. ACTUAL	.0700																																																																
MIN. MEAS. OVER PINS	1.2542 REF.																																																																
PIN DIAMETER	.080																																																																
<b>RZR S Front</b>	1332637		<table border="1"> <tr><td colspan="2">ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)</td></tr> <tr><td>NO. OF TEETH</td><td>26</td></tr> <tr><td>PITCH</td><td>24/48</td></tr> <tr><td>MODULE</td><td>1.05833</td></tr> <tr><td>PRESSURE ANGLE</td><td>45°</td></tr> <tr><td>PITCH DIA.</td><td>27.516 REF.</td></tr> <tr><td>BASE DIA.</td><td>19.467 REF.</td></tr> <tr><td>FORM DIA.</td><td>26.772</td></tr> <tr><td>MAJOR DIA.</td><td>28.575/28.448</td></tr> <tr><td>MINOR DIA. MIN</td><td>26.213</td></tr> <tr><td>MAX EFFECTIVE</td><td>1.875</td></tr> <tr><td>MIN ACTUAL</td><td>1.806</td></tr> <tr><td>CLASS</td><td>5</td></tr> <tr><td>PIN DIA.</td><td>2.032</td></tr> <tr><td>M. O. P. AFTER H. T.</td><td>30.874/30.940</td></tr> </table>	ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)		NO. OF TEETH	26	PITCH	24/48	MODULE	1.05833	PRESSURE ANGLE	45°	PITCH DIA.	27.516 REF.	BASE DIA.	19.467 REF.	FORM DIA.	26.772	MAJOR DIA.	28.575/28.448	MINOR DIA. MIN	26.213	MAX EFFECTIVE	1.875	MIN ACTUAL	1.806	CLASS	5	PIN DIA.	2.032	M. O. P. AFTER H. T.	30.874/30.940	<table border="1"> <tr><td colspan="2">ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)</td></tr> <tr><td>NO. OF TEETH</td><td>22</td></tr> <tr><td>PITCH</td><td>24/48</td></tr> <tr><td>MODULE</td><td>1.0583</td></tr> <tr><td>PRESSURE ANGLE</td><td>45°</td></tr> <tr><td>PITCH DIA.</td><td>23.284 REF.</td></tr> <tr><td>BASE DIA.</td><td>16.464 REF.</td></tr> <tr><td>FORM DIA.</td><td>22.530</td></tr> <tr><td>MAJOR DIA.</td><td>24.333/24.206</td></tr> <tr><td>MINOR DIA. MIN</td><td>21.996</td></tr> <tr><td>MAX EFFECTIVE</td><td>1.875</td></tr> <tr><td>MIN ACTUAL</td><td>1.808</td></tr> <tr><td>CLASS</td><td>5</td></tr> <tr><td>PIN DIA.</td><td>2.032</td></tr> <tr><td>M. O. P. AFTER H. T.</td><td>26.637/26.698</td></tr> </table>	ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)		NO. OF TEETH	22	PITCH	24/48	MODULE	1.0583	PRESSURE ANGLE	45°	PITCH DIA.	23.284 REF.	BASE DIA.	16.464 REF.	FORM DIA.	22.530	MAJOR DIA.	24.333/24.206	MINOR DIA. MIN	21.996	MAX EFFECTIVE	1.875	MIN ACTUAL	1.808	CLASS	5	PIN DIA.	2.032	M. O. P. AFTER H. T.	26.637/26.698	
ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)																																																																	
NO. OF TEETH	26																																																																
PITCH	24/48																																																																
MODULE	1.05833																																																																
PRESSURE ANGLE	45°																																																																
PITCH DIA.	27.516 REF.																																																																
BASE DIA.	19.467 REF.																																																																
FORM DIA.	26.772																																																																
MAJOR DIA.	28.575/28.448																																																																
MINOR DIA. MIN	26.213																																																																
MAX EFFECTIVE	1.875																																																																
MIN ACTUAL	1.806																																																																
CLASS	5																																																																
PIN DIA.	2.032																																																																
M. O. P. AFTER H. T.	30.874/30.940																																																																
ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)																																																																	
NO. OF TEETH	22																																																																
PITCH	24/48																																																																
MODULE	1.0583																																																																
PRESSURE ANGLE	45°																																																																
PITCH DIA.	23.284 REF.																																																																
BASE DIA.	16.464 REF.																																																																
FORM DIA.	22.530																																																																
MAJOR DIA.	24.333/24.206																																																																
MINOR DIA. MIN	21.996																																																																
MAX EFFECTIVE	1.875																																																																
MIN ACTUAL	1.808																																																																
CLASS	5																																																																
PIN DIA.	2.032																																																																
M. O. P. AFTER H. T.	26.637/26.698																																																																

	ASM #	Half Shaft Splines	Outer CV Splines	Inner CV Splines	Plunge/Angle Diagram																																																																
RZR XP Front	1332825		<table border="1"> <thead> <tr> <th colspan="2">WHEEL HUB INTERFACE</th> </tr> </thead> <tbody> <tr> <td colspan="2">EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT</td> </tr> <tr> <td>NO. OF TEETH</td> <td>26</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>1.0833 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>.766 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>1.0560</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>1.1250/1.1150</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>1.0320 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0700</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>1.2135 REF.</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	WHEEL HUB INTERFACE		EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT		NO. OF TEETH	26	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	1.0833 REF.	BASE DIAMETER	.766 REF.	FORM DIAMETER	1.0560	MAJOR DIAMETER	1.1250/1.1150	MINOR DIAMETER	1.0320 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0700	MIN. MEAS. OVER PINS	1.2135 REF.	PIN DIAMETER	.080	<table border="1"> <thead> <tr> <th colspan="2">DIFFERENTIAL INTERFACE</th> </tr> </thead> <tbody> <tr> <td colspan="2">ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)</td> </tr> <tr> <td>NO. OF TEETH</td> <td>22</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>.9167 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>.6482 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>.8870</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>.9580 / .9480</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>.866 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0701</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>1.0477 REF.</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	DIFFERENTIAL INTERFACE		ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)		NO. OF TEETH	22	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	.9167 REF.	BASE DIAMETER	.6482 REF.	FORM DIAMETER	.8870	MAJOR DIAMETER	.9580 / .9480	MINOR DIAMETER	.866 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0701	MIN. MEAS. OVER PINS	1.0477 REF.	PIN DIAMETER	.080	<p>DOJ PLUNGE &amp; ANGLE DIAGRAM</p>				
WHEEL HUB INTERFACE																																																																					
EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT																																																																					
NO. OF TEETH	26																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	1.0833 REF.																																																																				
BASE DIAMETER	.766 REF.																																																																				
FORM DIAMETER	1.0560																																																																				
MAJOR DIAMETER	1.1250/1.1150																																																																				
MINOR DIAMETER	1.0320 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0700																																																																				
MIN. MEAS. OVER PINS	1.2135 REF.																																																																				
PIN DIAMETER	.080																																																																				
DIFFERENTIAL INTERFACE																																																																					
ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)																																																																					
NO. OF TEETH	22																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	.9167 REF.																																																																				
BASE DIAMETER	.6482 REF.																																																																				
FORM DIAMETER	.8870																																																																				
MAJOR DIAMETER	.9580 / .9480																																																																				
MINOR DIAMETER	.866 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0701																																																																				
MIN. MEAS. OVER PINS	1.0477 REF.																																																																				
PIN DIAMETER	.080																																																																				
RZR XP Rear	1332826		<table border="1"> <thead> <tr> <th colspan="2">WHEEL HUB INTERFACE</th> </tr> </thead> <tbody> <tr> <td colspan="2">EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT</td> </tr> <tr> <td>NO. OF TEETH</td> <td>26</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>1.0833 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>.766 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>1.0560</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>1.1250/1.1150</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>1.0320 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0702</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>1.2135 REF.</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	WHEEL HUB INTERFACE		EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT		NO. OF TEETH	26	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	1.0833 REF.	BASE DIAMETER	.766 REF.	FORM DIAMETER	1.0560	MAJOR DIAMETER	1.1250/1.1150	MINOR DIAMETER	1.0320 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0702	MIN. MEAS. OVER PINS	1.2135 REF.	PIN DIAMETER	.080	<table border="1"> <thead> <tr> <th colspan="2">DIFFERENTIAL INTERFACE</th> </tr> </thead> <tbody> <tr> <td colspan="2">ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)</td> </tr> <tr> <td>NO. OF TEETH</td> <td>28</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>1.1666 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>.8250 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>1.1370</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>1.2087/1.1980</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>1.115 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0700</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>1.2978 REF.</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	DIFFERENTIAL INTERFACE		ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)		NO. OF TEETH	28	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	1.1666 REF.	BASE DIAMETER	.8250 REF.	FORM DIAMETER	1.1370	MAJOR DIAMETER	1.2087/1.1980	MINOR DIAMETER	1.115 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0700	MIN. MEAS. OVER PINS	1.2978 REF.	PIN DIAMETER	.080					
WHEEL HUB INTERFACE																																																																					
EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT																																																																					
NO. OF TEETH	26																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	1.0833 REF.																																																																				
BASE DIAMETER	.766 REF.																																																																				
FORM DIAMETER	1.0560																																																																				
MAJOR DIAMETER	1.1250/1.1150																																																																				
MINOR DIAMETER	1.0320 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0702																																																																				
MIN. MEAS. OVER PINS	1.2135 REF.																																																																				
PIN DIAMETER	.080																																																																				
DIFFERENTIAL INTERFACE																																																																					
ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)																																																																					
NO. OF TEETH	28																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	1.1666 REF.																																																																				
BASE DIAMETER	.8250 REF.																																																																				
FORM DIAMETER	1.1370																																																																				
MAJOR DIAMETER	1.2087/1.1980																																																																				
MINOR DIAMETER	1.115 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0700																																																																				
MIN. MEAS. OVER PINS	1.2978 REF.																																																																				
PIN DIAMETER	.080																																																																				
Scrambler Fr.	1332882		<table border="1"> <thead> <tr> <th colspan="2">WHEEL HUB INTERFACE</th> </tr> </thead> <tbody> <tr> <td colspan="2">EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT</td> </tr> <tr> <td>NO. OF TEETH</td> <td>20</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>.8333 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>.5893 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>.806</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>.875 / .865</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>.782 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0702</td> </tr> <tr> <td>MAX. MEAS. OVER PINS</td> <td>.9655 REF.</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>.9643</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	WHEEL HUB INTERFACE		EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT		NO. OF TEETH	20	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	.8333 REF.	BASE DIAMETER	.5893 REF.	FORM DIAMETER	.806	MAJOR DIAMETER	.875 / .865	MINOR DIAMETER	.782 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0702	MAX. MEAS. OVER PINS	.9655 REF.	MIN. MEAS. OVER PINS	.9643	PIN DIAMETER	.080	<table border="1"> <thead> <tr> <th colspan="2">DIFFERENTIAL INTERFACE</th> </tr> </thead> <tbody> <tr> <td colspan="2">ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)</td> </tr> <tr> <td>NO. OF TEETH</td> <td>22</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>.9167 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>.6482 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>.8870</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>.9580 / .9480</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>.866 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0701</td> </tr> <tr> <td>MAX. MEAS. OVER PINS</td> <td>1.0494 REF.</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>1.0477</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	DIFFERENTIAL INTERFACE		ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)		NO. OF TEETH	22	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	.9167 REF.	BASE DIAMETER	.6482 REF.	FORM DIAMETER	.8870	MAJOR DIAMETER	.9580 / .9480	MINOR DIAMETER	.866 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0701	MAX. MEAS. OVER PINS	1.0494 REF.	MIN. MEAS. OVER PINS	1.0477	PIN DIAMETER	.080	
WHEEL HUB INTERFACE																																																																					
EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT																																																																					
NO. OF TEETH	20																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	.8333 REF.																																																																				
BASE DIAMETER	.5893 REF.																																																																				
FORM DIAMETER	.806																																																																				
MAJOR DIAMETER	.875 / .865																																																																				
MINOR DIAMETER	.782 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0702																																																																				
MAX. MEAS. OVER PINS	.9655 REF.																																																																				
MIN. MEAS. OVER PINS	.9643																																																																				
PIN DIAMETER	.080																																																																				
DIFFERENTIAL INTERFACE																																																																					
ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)																																																																					
NO. OF TEETH	22																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	.9167 REF.																																																																				
BASE DIAMETER	.6482 REF.																																																																				
FORM DIAMETER	.8870																																																																				
MAJOR DIAMETER	.9580 / .9480																																																																				
MINOR DIAMETER	.866 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0701																																																																				
MAX. MEAS. OVER PINS	1.0494 REF.																																																																				
MIN. MEAS. OVER PINS	1.0477																																																																				
PIN DIAMETER	.080																																																																				

	ASM #	Half Shaft Splines	Outer CV Splines	Inner CV Splines	Plunge/Angle Diagram																																																																
SPM Rr.	1332935		<table border="1"> <thead> <tr> <th colspan="2">DIFFERENTIAL INTERFACE</th> </tr> </thead> <tbody> <tr> <td colspan="2">ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)</td> </tr> <tr> <td>NO. OF TEETH</td> <td>26</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>1.0833 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>.766 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>1.0560</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>1.1250/1.1150</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>1.0320 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0702</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>1.2155 REF.</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	DIFFERENTIAL INTERFACE		ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)		NO. OF TEETH	26	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	1.0833 REF.	BASE DIAMETER	.766 REF.	FORM DIAMETER	1.0560	MAJOR DIAMETER	1.1250/1.1150	MINOR DIAMETER	1.0320 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0702	MIN. MEAS. OVER PINS	1.2155 REF.	PIN DIAMETER	.080	<table border="1"> <thead> <tr> <th colspan="2">DOJ STEM EXTERNAL SPLINE</th> </tr> </thead> <tbody> <tr> <td colspan="2">ANSI B92.1 EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT</td> </tr> <tr> <td>NO. OF TEETH</td> <td>36</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>1.5000 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>1.0607 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>1.4710</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>1.5420/1.5320</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>1.448 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0698</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>1.6312 REF.</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	DOJ STEM EXTERNAL SPLINE		ANSI B92.1 EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT		NO. OF TEETH	36	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	1.5000 REF.	BASE DIAMETER	1.0607 REF.	FORM DIAMETER	1.4710	MAJOR DIAMETER	1.5420/1.5320	MINOR DIAMETER	1.448 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0698	MIN. MEAS. OVER PINS	1.6312 REF.	PIN DIAMETER	.080	<p>Plunge/Angle Diagram for SPM Rr. The graph plots Joint Angle (0° to 30°) against distance from the center (EXTEND to COLLAPSE). Key points include (1.36, 30°) for Retention Clip Interference and (.74, 30°) for Bell Bottom Interference. A 75° Axle Interference is also indicated.</p>				
DIFFERENTIAL INTERFACE																																																																					
ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)																																																																					
NO. OF TEETH	26																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	1.0833 REF.																																																																				
BASE DIAMETER	.766 REF.																																																																				
FORM DIAMETER	1.0560																																																																				
MAJOR DIAMETER	1.1250/1.1150																																																																				
MINOR DIAMETER	1.0320 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0702																																																																				
MIN. MEAS. OVER PINS	1.2155 REF.																																																																				
PIN DIAMETER	.080																																																																				
DOJ STEM EXTERNAL SPLINE																																																																					
ANSI B92.1 EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT																																																																					
NO. OF TEETH	36																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	1.5000 REF.																																																																				
BASE DIAMETER	1.0607 REF.																																																																				
FORM DIAMETER	1.4710																																																																				
MAJOR DIAMETER	1.5420/1.5320																																																																				
MINOR DIAMETER	1.448 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0698																																																																				
MIN. MEAS. OVER PINS	1.6312 REF.																																																																				
PIN DIAMETER	.080																																																																				
SPM Fr.	1332881		<table border="1"> <thead> <tr> <th colspan="2">WHEEL HUB INTERFACE</th> </tr> </thead> <tbody> <tr> <td colspan="2">EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT</td> </tr> <tr> <td>NO. OF TEETH</td> <td>20</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>.8333 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>.5893 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>.806</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>.875/.865</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>.782 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0702</td> </tr> <tr> <td>MAX. MEAS. OVER PINS</td> <td>.9655 REF.</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>.9643</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	WHEEL HUB INTERFACE		EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT		NO. OF TEETH	20	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	.8333 REF.	BASE DIAMETER	.5893 REF.	FORM DIAMETER	.806	MAJOR DIAMETER	.875/.865	MINOR DIAMETER	.782 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0702	MAX. MEAS. OVER PINS	.9655 REF.	MIN. MEAS. OVER PINS	.9643	PIN DIAMETER	.080	<table border="1"> <thead> <tr> <th colspan="2">DIFFERENTIAL INTERFACE</th> </tr> </thead> <tbody> <tr> <td colspan="2">ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)</td> </tr> <tr> <td>NO. OF TEETH</td> <td>22</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>.9167 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>.6482 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>.8870</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>.9580/.9480</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>.866 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0701</td> </tr> <tr> <td>MAX. MEAS. OVER PINS</td> <td>1.0494 REF.</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>1.0477</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	DIFFERENTIAL INTERFACE		ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)		NO. OF TEETH	22	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	.9167 REF.	BASE DIAMETER	.6482 REF.	FORM DIAMETER	.8870	MAJOR DIAMETER	.9580/.9480	MINOR DIAMETER	.866 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0701	MAX. MEAS. OVER PINS	1.0494 REF.	MIN. MEAS. OVER PINS	1.0477	PIN DIAMETER	.080	<p>Plunge/Angle Diagram for SPM Fr. The graph plots Joint Angle (0° to 30°) against distance from the center (EXTEND to COLLAPSE). Key points include (1.36, 30°) for Retention Clip Interference and (.74, 30°) for Bell Bottom Interference. A 75° Axle Interference is also indicated.</p>
WHEEL HUB INTERFACE																																																																					
EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT																																																																					
NO. OF TEETH	20																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	.8333 REF.																																																																				
BASE DIAMETER	.5893 REF.																																																																				
FORM DIAMETER	.806																																																																				
MAJOR DIAMETER	.875/.865																																																																				
MINOR DIAMETER	.782 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0702																																																																				
MAX. MEAS. OVER PINS	.9655 REF.																																																																				
MIN. MEAS. OVER PINS	.9643																																																																				
PIN DIAMETER	.080																																																																				
DIFFERENTIAL INTERFACE																																																																					
ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)																																																																					
NO. OF TEETH	22																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	.9167 REF.																																																																				
BASE DIAMETER	.6482 REF.																																																																				
FORM DIAMETER	.8870																																																																				
MAJOR DIAMETER	.9580/.9480																																																																				
MINOR DIAMETER	.866 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0701																																																																				
MAX. MEAS. OVER PINS	1.0494 REF.																																																																				
MIN. MEAS. OVER PINS	1.0477																																																																				
PIN DIAMETER	.080																																																																				
RGR Rr.	1333008		<table border="1"> <thead> <tr> <th colspan="2">WHEEL HUB INTERFACE</th> </tr> </thead> <tbody> <tr> <td colspan="2">EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT</td> </tr> <tr> <td>NO. OF TEETH</td> <td>26</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>1.0833 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>.766 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>1.0560</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>1.1250/1.1150</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>1.0320 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0702</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>1.2135 REF.</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	WHEEL HUB INTERFACE		EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT		NO. OF TEETH	26	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	1.0833 REF.	BASE DIAMETER	.766 REF.	FORM DIAMETER	1.0560	MAJOR DIAMETER	1.1250/1.1150	MINOR DIAMETER	1.0320 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0702	MIN. MEAS. OVER PINS	1.2135 REF.	PIN DIAMETER	.080	<table border="1"> <thead> <tr> <th colspan="2">DIFFERENTIAL INTERFACE</th> </tr> </thead> <tbody> <tr> <td colspan="2">ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)</td> </tr> <tr> <td>NO. OF TEETH</td> <td>28</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>1.1666 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>.8250 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>1.1370</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>1.2080/1.1980</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>1.115 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0700</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>1.2978 REF.</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	DIFFERENTIAL INTERFACE		ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)		NO. OF TEETH	28	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	1.1666 REF.	BASE DIAMETER	.8250 REF.	FORM DIAMETER	1.1370	MAJOR DIAMETER	1.2080/1.1980	MINOR DIAMETER	1.115 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0700	MIN. MEAS. OVER PINS	1.2978 REF.	PIN DIAMETER	.080	<p>Plunge/Angle Diagram for RGR Rr. The graph plots Joint Angle (0° to 30°) against distance from the center (EXTEND to COLLAPSE). Key points include (1.36, 30°) for Retention Clip Interference and (.74, 30°) for Bell Bottom Interference. A 75° Axle Interference is also indicated.</p>				
WHEEL HUB INTERFACE																																																																					
EXTERNAL INVOLUTE SPLINE (HARDENED) FILLET ROOT SIDE FIT																																																																					
NO. OF TEETH	26																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	1.0833 REF.																																																																				
BASE DIAMETER	.766 REF.																																																																				
FORM DIAMETER	1.0560																																																																				
MAJOR DIAMETER	1.1250/1.1150																																																																				
MINOR DIAMETER	1.0320 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0702																																																																				
MIN. MEAS. OVER PINS	1.2135 REF.																																																																				
PIN DIAMETER	.080																																																																				
DIFFERENTIAL INTERFACE																																																																					
ANSI B92.1 EXTERNAL INVOLUTE SPLINE FILLET ROOT SIDE FIT (HARDENED)																																																																					
NO. OF TEETH	28																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	1.1666 REF.																																																																				
BASE DIAMETER	.8250 REF.																																																																				
FORM DIAMETER	1.1370																																																																				
MAJOR DIAMETER	1.2080/1.1980																																																																				
MINOR DIAMETER	1.115 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0700																																																																				
MIN. MEAS. OVER PINS	1.2978 REF.																																																																				
PIN DIAMETER	.080																																																																				

	ASM #	Half Shaft Splines	Outer CV Splines	Inner CV Splines	Plunge/Angle Diagram																																																																
SPM 300 Rr.	1332341		<table border="1"> <thead> <tr> <th colspan="2">OUTBOARD BELL STEM DETAIL</th> </tr> <tr> <th colspan="2">EXTERNAL INVOLUTE SPLINE (HARDENED)</th> </tr> <tr> <th colspan="2">FILLET ROOT SIDE FIT</th> </tr> </thead> <tbody> <tr> <td>NO. OF TEETH</td> <td>20</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>45°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>8.333 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>5.893 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>.806</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>.875/ .870</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>.780 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0738</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0702</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>9.643 REF.</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	OUTBOARD BELL STEM DETAIL		EXTERNAL INVOLUTE SPLINE (HARDENED)		FILLET ROOT SIDE FIT		NO. OF TEETH	20	PITCH	24/48	PRESSURE ANGLE	45°	PITCH DIAMETER	8.333 REF.	BASE DIAMETER	5.893 REF.	FORM DIAMETER	.806	MAJOR DIAMETER	.875/ .870	MINOR DIAMETER	.780 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0738	MIN. ACTUAL	.0702	MIN. MEAS. OVER PINS	9.643 REF.	PIN DIAMETER	.080	<table border="1"> <thead> <tr> <th colspan="2">INBOARD BELL STEM DETAIL</th> </tr> <tr> <th colspan="2">EXTERNAL INVOLUTE SPLINE (HARDENED)</th> </tr> <tr> <th colspan="2">FILLET ROOT SIDE FIT</th> </tr> </thead> <tbody> <tr> <td>NO. OF TEETH</td> <td>20</td> </tr> <tr> <td>PITCH</td> <td>24/48</td> </tr> <tr> <td>PRESSURE ANGLE</td> <td>30°</td> </tr> <tr> <td>PITCH DIAMETER</td> <td>8.333 REF.</td> </tr> <tr> <td>BASE DIAMETER</td> <td>7.217 REF.</td> </tr> <tr> <td>FORM DIAMETER</td> <td>.767</td> </tr> <tr> <td>MAJOR DIAMETER</td> <td>.875/ .870</td> </tr> <tr> <td>MINOR DIAMETER</td> <td>.733 MIN.</td> </tr> <tr> <td colspan="2">CIRC. TOOTH THICKNESS</td> </tr> <tr> <td>MAX. EFFECTIVE</td> <td>.0654</td> </tr> <tr> <td>MIN. ACTUAL</td> <td>.0618</td> </tr> <tr> <td>MIN. MEAS. OVER PINS</td> <td>9.513 REF.</td> </tr> <tr> <td>PIN DIAMETER</td> <td>.080</td> </tr> </tbody> </table>	INBOARD BELL STEM DETAIL		EXTERNAL INVOLUTE SPLINE (HARDENED)		FILLET ROOT SIDE FIT		NO. OF TEETH	20	PITCH	24/48	PRESSURE ANGLE	30°	PITCH DIAMETER	8.333 REF.	BASE DIAMETER	7.217 REF.	FORM DIAMETER	.767	MAJOR DIAMETER	.875/ .870	MINOR DIAMETER	.733 MIN.	CIRC. TOOTH THICKNESS		MAX. EFFECTIVE	.0654	MIN. ACTUAL	.0618	MIN. MEAS. OVER PINS	9.513 REF.	PIN DIAMETER	.080	<p>PLUNGE &amp; ANGLE DIAGRAM REF.</p> <p>12.62 12.68 12.75 12.81 12.87 JOINT CENTER TO JOINT CENTER</p> <p>JOINT ANGLE</p> <p>5° 10° 15° 20° 25° 30° 35° 40° 45°</p>
OUTBOARD BELL STEM DETAIL																																																																					
EXTERNAL INVOLUTE SPLINE (HARDENED)																																																																					
FILLET ROOT SIDE FIT																																																																					
NO. OF TEETH	20																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	45°																																																																				
PITCH DIAMETER	8.333 REF.																																																																				
BASE DIAMETER	5.893 REF.																																																																				
FORM DIAMETER	.806																																																																				
MAJOR DIAMETER	.875/ .870																																																																				
MINOR DIAMETER	.780 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0738																																																																				
MIN. ACTUAL	.0702																																																																				
MIN. MEAS. OVER PINS	9.643 REF.																																																																				
PIN DIAMETER	.080																																																																				
INBOARD BELL STEM DETAIL																																																																					
EXTERNAL INVOLUTE SPLINE (HARDENED)																																																																					
FILLET ROOT SIDE FIT																																																																					
NO. OF TEETH	20																																																																				
PITCH	24/48																																																																				
PRESSURE ANGLE	30°																																																																				
PITCH DIAMETER	8.333 REF.																																																																				
BASE DIAMETER	7.217 REF.																																																																				
FORM DIAMETER	.767																																																																				
MAJOR DIAMETER	.875/ .870																																																																				
MINOR DIAMETER	.733 MIN.																																																																				
CIRC. TOOTH THICKNESS																																																																					
MAX. EFFECTIVE	.0654																																																																				
MIN. ACTUAL	.0618																																																																				
MIN. MEAS. OVER PINS	9.513 REF.																																																																				
PIN DIAMETER	.080																																																																				